

EHC™ Group II base stocks expected in 2019

EHC™ base stocks comprise a global Group II slate as defined within API/ATIEL guidelines for formulation and qualification of automotive lubricants. With base oil interchange and viscosity grade read-across capabilities, EHC base stocks offer broad coverage that enables supply chain flexibility and simplified qualification testing requirements. EHC base stocks may also be used in industrial and marine applications where formulations benefit from increased oxidation stability and higher viscosity index (VI). Our rigorous processes ensure reliable delivery of consistent quality base stocks.

ExxonMobil

Key benefits

Consistent quality to help formulators produce high-performance blends that:



Meet or exceed
industry
requirements



Achieve exceptional
oxidation stability



Meet or exceed
engine oil quality
requirements

Energy lives here™

Sales specifications and availability expected in 2019

Sales specifications			EHC™ 45	EHC™ 50	EHC™ 65	EHC™ 110	EHC™ 120
Property	Limits	Standard method (a)					
Appearance		Visual	Clear and bright				
ASTM color	Max	ASTM D1500	L0.5	0.5	L0.5	0.5	0.5
CCS viscosity -25°C mPa•sec	Max	ASTM D5293	1550				
CCS viscosity -20°C mPa•sec	Max	ASTM D5293		1500	3100		
Flash point, COC Deg C	Min	ASTM D92	204	210	214	230	255
Kinematic viscosity @ 100°C mm2/sec	Min-Max	ASTM D445	4.4-4.7	5.2-5.6	6.3-6.6	10.0-12.0	11.1-12.7
NOACK Volatility, wt%	Max	ASTM D5800	15	13.5	10		
Pour point, Deg C	Max	ASTM D97	-18	-18	-18	-15	-15
Viscosity index	Min-Max	ASTM D2270	113-119	110-119	103-109	95-110	105-115

Availability	EHC™ 45	EHC™ 50	EHC™ 65	EHC™ 110	EHC™ 120
Americas	■		■		■
Europe, Africa, Middle East		■			■
Asia/Pacific		■		■	

(a) In lieu of standard test method, alternate test methods may be used for the certification of a product property.

Note 1: Products are certified on release to meet the values specified. Actual values may deviate within the established reproducibility of the test method specified.

Note 2: For purpose of determining conformance with specification, observed or calculated values shall be rounded off to the nearest unit in the last significant digit used in expressing the limiting value in accordance to the ASTM E 29 method.

Health and Safety

Detailed health and safety information for this product is provided in the material safety data sheet (MSDS), available upon request through your local sales representative or from www.ExxonMobil.com.

2-2017

exxonmobil.com/basestocks

All products may not be available in all countries. Every care has been taken in the preparation of this information. Typical values may vary within modest ranges, and specifications may be subject to change. To the extent permitted by applicable law, all warranties and/or representations, express or implied, as to the accuracy of the information are disclaimed, and no liability is accepted for the accuracy or completeness of the same.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names which include Esso, Mobil, Exxon, or ExxonMobil. For convenience and simplicity, the term ExxonMobil may be used to represent all of these entities, and the products and services provided by those entities. Nothing in this brochure is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with local ExxonMobil-affiliated entities.

© 2017 ExxonMobil. All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries.