

Mobil Delvac™ 1600 Series

Heavy duty monograde lubricants

Mobil Delvac™ 1630 and Mobil Delvac™ 1640 are high performance oils designed to meet or exceed the requirements of diesel engine manufacturers, as well as a wide range of applications where a monograde lubricant is advised.

They are formulated from advanced technology base oils and a balanced additive system, which provide exceptional performance in both modern and older model diesel engines. The oils provide resistance to lacquer formation on cylinder liners.

The lubricants are recommended for intercooled, turbo-charged engines operating under severe conditions. This includes the main engines of a number of harbour craft and high speed ferries, and a range of diesel powered equipment, such as deck generators.

Lower inventory storage costs

The Mobil Delvac™ 1600 range has outstanding protection against oil thickening, high temperature deposits, sludge build-up and oil degradation.

It provides:

- Long oil life above manufacturer recommended oil drain intervals
- Maximised protection against ring sticking
- Superior control of high temperature deposits



Outstanding engine life

Mobil Delvac 1630 and Mobil Delvac 1640 can provide:

- Excellent soot handling capabilities, which maintain viscosity control and minimise wear – this can potentially curb energy consumption while enhancing system responsiveness
- Exceptional wear protection, which can control maintenance costs while extending engine life

For more information on Mobil Delvac 1600 Series, please contact your ExxonMobil Marine Fuels & Lubricants representative or visit www.exxonmobil.com/marine