



White paper

# Environmentally acceptable lubricants: Performance and regulatory compliance



Frithjof Metzner, Technology Solution Professional,  
Marine and Gas Engine Oils

# Table of contents

Introduction	3
01 – An evolving operational environment	4
02 – Industry concerns and challenges	6
The sheen rule	6
Sources of lead in used oil	7
03 – Environmentally Acceptable Lubricants (EAL)	8
EAL characteristics explained	8
Base stock benefits	9
Synthetic esters: specific properties	10
04 – A global drive to minimise marine pollution	11
05 – ExxonMobil’s EAL offering	12
06 – Compliance is just the start	13

## **Introduction**

The U.S. Environmental Protection Agency's (EPA) Vessel General Permit (VGP) regulation has a significant impact on marine operators' lubricant selection. The 2018 Vessels Incidental Discharge Act (VIDA) is expected to replace the 2013 VGP in 2026. If implemented, it will affect an expanded scope of equipment.

This paper examines key industry concerns, provides clarity regarding Environmentally Acceptable Lubricants (EALs) and guides EAL selection based on application.

# An evolving operational environment

The combination of environmental regulations — pressure from manufacturers and the supply chain — and customer demand for “green” products, attributes and services; continues to have a significant impact on the marine industry. Although the current major focus is fuel and emission challenges, changes are also affecting a wide range of lubricant applications.





The continued application of the VGP affects almost all vessels longer than 79 feet operating within three nautical miles of the U.S. coastline and within U.S. jurisdiction in the Great Lakes and inland waters.

It sets out detailed rules for discharges from oil-to-sea interfaces that affects around 70,000 vessels annually. Specifically, it mandates the use of EALs for certain applications. Non-compliance risks a fine of up to \$25,000 per day, up to one year of imprisonment or both.

The VIDA, signed into U.S. law in December 2018, was intended to replace the VGP and streamline the patchwork of federal, state and local requirements for the commercial vessel community. The VIDA amendment of the Clean Water Act provides for new performance standards to be developed by the EPA and implementation regulations to be developed by the U.S. Coast Guard; until then, the 2013 VGP applies.

## The oil-to-sea interface

Oil-to-sea interfaces include any onboard equipment where seals or surfaces have the potential to release oil into the sea. The VGP specifically identifies a range of equipment that has the potential for lubrication discharge from an oil-to-sea interface. These include the equipment below but is extended to any equipment on deck that reaches outboard:

- Controllable pitch propellers
- Thrusters
- Stern tubes
- Thruster bearings
- Stabilisers
- Rudder bearings
- Azimuth thrusters
- Propulsion pods
- Wire ropes and cables
- Equipment subject to immersion
- Hydraulic hose-handling cranes
- Hydraulic provision cranes
- Hydraulic stern ramps

Certain types of seals, such as the air seals for stern tubes, are not considered to be an oil-to-sea interface as under normal circumstances they do not allow lubricant release.

The VIDA does not list specific applications but defines the oil-to-sea interface as any equipment that has the potential to release oil into the water. Contact your ExxonMobil Marine Field Engineer representative for further details or consult the ASTM D8324 Standard Guide for Selection of Environmentally Acceptable Lubricants for the U.S. Environmental Protection Agency (EPA) Vessel General Permit.

## Industry concerns and challenges

### The sheen rule

Vessels operating in U.S. inland and coastal waters are also regulated by the Clean Water Act Discharge of Oil regulation, which is more generally known as the “sheen rule”. This commonly used name has given rise to a widespread misperception that oil spills that do not leave a sheen are acceptable. This is not the case. The regulation requires any vessel that discharges oil that could be “harmful to the public health or welfare or the environment” to report the spill.

It also establishes the measures for determining whether an oil spill needs to be reported. The criteria are discharges that:

- Cause a sheen or discoloration on the surface of the water or adjoining shorelines
- Violate applicable water-quality standards
- Cause a sludge or emulsion to form below the water surface or on adjoining shorelines

According to the EPA, the use of EALs does not provide a waiver to the rule, although it may minimise the risk of triggering the reporting requirements.

# Sources of lead in used oil

Another common misperception involves the presence of lead in used stern tube oil samples, which has been accredited to the lubricant's formulation. Routine oil analysis has recently revealed that a small percentage of vessels have increased lead content in their used oil, above the International Association of Classification Societies (IACS) guidelines (10mg/kg). Since lead is a heavy metal and is not generated by chemical reaction, the source of the lead could be:

- Stern tube bearing wear, depending on composition
- From paints or coatings within oil circulation systems
- Acidic corrosion of the lead element within the stern tube
- Additives in the EAL
- Other sources, including contamination

A significant number of the vessels that have reported the high lead levels have tin bearings. There have been no reported operational issues and lubricant analysis had revealed no leaching effect as a result of oil formulation.

If high levels of lead are detected, vessel operators should consult with their OEMs to identify the source of the contamination in order to ensure the most appropriate remedial action is taken.

# Environmentally Acceptable Lubricants (EAL)

EALs are defined in the VGP as lubricants that are biodegradable, minimally toxic and non-bioaccumulative.

To meet these environmental standards, an oil must meet all three criteria — and there are comprehensive parameters for each classification. What is not specified, however, is an oil's chemistry. As a result, a number of base stocks can be used, including:

- Polyalkylene glycol
- Triglycerides
- Synthetic esters

It is also possible to employ sea water, in selected and limited applications, but this requires the use of bearings made from self-lubricating elastomeric polymer. Practical experience of this type of installation shows cases of rapid wear, or even malfunctions, some of which may be caused by insufficient lubricant flow or a buildup of particulate matter.

Although all these options meet the criteria of the VGP, not all EALs are created equal.

## EAL characteristics explained

### Biodegradable:

As per the Organisation for Economic Cooperation and Development (OECD) Biodegradation 301B test, the lubricant must meet a minimum of 60% biodegradation within 28 days for 90% of an oil formulation or 75% of a grease formulation.

### Minimally toxic:

The lubricant must pass the OECD 201, 202 and 203 acute toxicity tests or OECD 210 and OECD 211 for chronic toxicity. As an alternative, an evaluation may be conducted on a constituent basis.

### Non-bioaccumulative:

Bioaccumulation occurs when an organism absorbs a substance at a rate greater than the speed at which the substance is lost. This can be assessed using the OECD 201, 202 and 203 tests. These tests are part of the criteria used to determine whether a substance, like a lubricant component, is environmentally acceptable.

# Base stock benefits

Depending on composition, EALs based on polyalkylene glycol (PAG) offer good lubricity, load-bearing, viscosity indices, oxidation characteristics and hydrolytic stability. However, they are typically highly incompatible with conventional seals and filters, as well as hydrocarbon, vegetable and ester-based oils. This makes switching to a PAG-based EAL lubricant both complex and costly, as solvent washing of lubricant tanks and associated systems may be necessary and seals may need to be replaced.

Triglycerides, naturally derived vegetable-based lubricants, are readily biodegradable and offer excellent lubricity but are prone to hydrolysis. They also have poor resistance to temperature extremes, low oxidative stability and a short operational life.

The most effective and balanced EAL lubricants are based on synthetic ester base stocks. They perform well across a wide range of temperatures, have a high viscosity index, possess good lubricity, provide excellent corrosion protection and have high oxidative stability. They also offer excellent biodegradability and can have good hydrolytic stability depending on the ester.

They have a history of proven performance, long operational life and are generally compatible with mineral oils, making changeovers straightforward.

**For more detailed guidance, consult a Mobil expert.**



# Synthetic esters: specific properties



**Volatility:** The polarity of ester molecules causes them to be attracted to one another and because of this more energy (heat) is required to get them to move from a liquid to a gaseous state. As a result, the synthetic ester lubricants have a high flash point and a low rate of evaporation.



**Lubricity:** Polarity also causes the ester molecules to be attracted to positively charged metal surfaces. As a result, the molecules tend to create a film that requires additional energy (load) to wipe it off. The result is high lubricity and low energy consumption in lubricant applications.



**Detergency/Dispersancy:** The polar nature of esters makes them good solvents and dispersants. This allows the esters to dissolve or disperse oil degradation byproducts that might otherwise be deposited as varnish or sludge.



**Biodegradability:** The character of ester linkage provides vulnerability for microbes to biodegrade the ester molecule. This results in high biodegradability rates for ester lubricants, which enables the formulation of environmentally friendly products.

Although base stock is important, the lubricant's additive package also plays an important part in an EAL's overall performance. For example, the demands placed on hydraulic and gear oils are quite different. Gear oils often have to deal with below-the-waterline applications, such as thrusters and pitch propellers. Hydraulic oils are most commonly found in deck equipment, such as cranes, ramps and hatches.

Vessel operators are therefore advised to select lubricants best suited for individual tasks. This will not only ensure optimum operation, it can also help maintain lubricant performance, which can help reduce maintenance costs and enhance overall efficiencies.

# A global drive to minimise marine pollution

The VGP's ruling is part of a wider trend driven by a growing awareness of environmental issues and the demand from business to better understand potential impacts from supply chains. For example, the International Maritime Organization (IMO) Polar Code, which entered into effect 1 January 2017, recommends the use of EALs in polar waters.

There are also national and regional schemes that impose environmental standards for marine lubricants, including the European Union's Ecolabel, Germany's Blue Angel scheme, Sweden's SS 155434 ruling on hydraulic fluids and greases, and the Nordic Swan, which was jointly developed by Norway, Sweden, Iceland, Finland and Denmark. The Nordic Swan is generally considered to be the most demanding and comprehensive programme as it sets out criteria for biodegradability, toxicity, renewability and technical performance.

These types of regulations are an everyday reality for vessel operators and their scope and frequency are likely to increase. China, for instance, has been incrementally tightening its maritime emissions regulations and the IMO has indicated further changes.



# Mobil's EAL offering

In order to ensure that vessel operators have access to lubricants that not only comply with the VGP (and future VIDA requirements) but also help to extend equipment life (compared with industry-standard mineral products),

ExxonMobil has developed the Mobil SHC™ Aware™ family of high-performance synthetic ester-based EALs. These include hydraulic oils, synthetic gear oils, greases and stern tube oils.

The type of ester is selected by the application's requirements. We chose saturated ester for Mobil SHC™ Aware™ Gear Oil, Mobil SHC Aware™ H and Mobil SHC™ Aware™ Grease to ensure good resistance to temperature-related degradation and stability in the presence of water to protect against hydrolytic breakdown.

The presence of water in stern tubes can be unavoidable, so unsaturated esters are used in the formulation of Mobil SHC™ Aware™ ST Series lubricants. This ensures that the stern tube oils readily emulsify with water while providing outstanding lubrication and rust/corrosion protection, even with up to 20% water in a stable emulsion. For users who prefer draining off water from the stern tube system, SHC™ Aware™ Gear Series is a viable demulsifying alternative in Mobil's EAL offer.

# Regulatory Compliance is just the start

When it comes to EAL selection, regulatory compliance is just the starting point. Vessel operators should also look for lubricants that are most suitable for the application and can help to enhance operational efficiencies.

Conversion from existing mineral oils to EALs requires time in dry dock for some applications. It is therefore essential that the changeover process is as easy to manage as possible. Vessel operators will want to avoid the need for solvent flushing, as required for PAGs, while also ensuring that their EALs are up to the job. The optimal solution is an EAL based on synthetic esters, coupled with EAL-compliant performance additive technology.

## Used oil analysis

A condition-based maintenance approach, such as used oil analysis, offers a range of benefits. Properly implemented, it can help vessel operators:



**Improve  
equipment  
reliability**



**Cut lubricant  
consumption/  
expenditure**



**Reduce  
maintenance  
costs**



**Enhance  
equipment  
life**

ExxonMobil's Mobil™ Lubricant Analysis simplifies this process by producing reliable results and clear guidance that can help vessel operators identify issues before they become problems. Its insights into the condition of equipment and lubricants are backed by ExxonMobil's extensive marine industry experience and expertise.



[exxonmobil.com/marine](https://www.exxonmobil.com/marine)

© 2026 ExxonMobil. All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries.

The user may forward, distribute, and/or photocopy this copyrighted document only if unaltered and complete, including all of its headers, footers, disclaimers, and other information. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We based the information on data believed to be reliable on the date compiled, but we do not represent, warrant, or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, suitability, accuracy, reliability, or completeness of this information or the products, materials, or processes described. The user is solely responsible for all determinations regarding any use and any process.

We expressly disclaim liability for any loss, damage, or injury directly or indirectly suffered or incurred as a result of or related to anyone using or relying on any of the information in this document. There is no warranty against patent infringement, nor any endorsement of any product or process, and we expressly disclaim any contrary implication. The terms, "we", "our", "ExxonMobil Chemical", or "ExxonMobil" are used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates they directly or indirectly steward. The ExxonMobil Chemical Emblem, the "Interlocking X" Device, and Vistalon are trademarks of Exxon Mobil Corporation.

The images within this document are illustrative of types of vessels that may use EALs.