

Mobilgard™ HSD+ 15W-40

High-performance, heavy-duty diesel engine oil offering advanced protection



Energy lives here™

Product features

Mobilgard™ HSD+ 15W-40 is an advanced, multigrade diesel engine oil that can help extend engine life and is formulated for severe-service, high-speed diesel engines in marine applications. It can offer:

- Outstanding oxidation stability
- Excellent soot and viscosity control
- Component compatibility
- Low-ash (low SAPS*) formulation, meeting API CK-4 requirements

Performance up to **50%** beyond OEM-recommended ODIs†

Potential benefits

Mobilgard HSD+ 15W-40 engine oil can help:

- 1** Extend oil drain interval (ODI) capability†
- 2** Reduce low-temperature sludge buildup and high-temperature deposits
- 3** Provide greater engine efficiency, long engine life and long oil life
- 4** Protect life of exhaust after-treatment systems (DPF, DOC and SCR)

Engine recommendations

Fully backward compatible, Mobilgard HSD+ 15W-40 oil delivers exceptional performance in both newer and older heavy-duty engine designs. Accordingly, the oil meets or exceeds the requirements of API CK-4, Caterpillar ECF-3, and Cummins CES 20086 and 20081. Mobilgard HSD+ 15W-40 oil has secured the following OEM approvals: MAN M 3575, MAN M3275-1 and Volvo VDS-4.5.

Recommended applications

The latest heavy-duty engines, including those equipped with aftertreatment systems and EGR



The most severe-service marine applications of modern, high-speed diesel engines



*Sulphated Ash, Phosphorus and Sulphur

†Results may vary based on vessel/engine condition, load and environmental conditions. Consult OEM or ExxonMobil before implementing extended ODIs.

Mobilgard™ HSD+ 15W-40

Product formulation


Mobilgard™ HSD+ 15W-40 engine oil is formulated with optimised base oil technology, containing severely hydro-processed base stocks and a tailored additive system to deliver extended performance and oil drain intervals. This proprietary formulation delivers excellent wear protection, and outstanding oxidation stability and TBN retention.

Potential advantages

Mobilgard HSD+ 15W-40 oil also provides outstanding resistance to oil consumption, oxidation, corrosive and abrasive wear, and high-temperature deposits. The oil delivers excellent wear and engine protection, extended drain capability, outstanding high-temperature performance and engine cleanliness.

Engine protection

Developed in close collaboration with major OEMs, Mobilgard HSD+ 15W-40 oil is recommended for use in a wide range of heavy-duty applications and in the most severe marine environments. This product provides outstanding protection in the most demanding diesel engines.



Meets requirements of or approved by

Caterpillar	✓
Cummins	✓
Detroit	✓
Mercedes Benz	✓
MAN	✓
Volvo	✓

Typical properties

Mobilgard HSD+	
SAE Grade	15W-40
Viscosity, ASTM D 445	
cSt @ 40°C	109
cSt @ 100°C	14.1
Viscosity Index, ASTM D 2270	130
Density @ 15°C kg/L, ASTM D 4052	0.874
Pour Point, °C, ASTM D 97	-33
Flash Point, °C, ASTM D 92	225
Sulphated Ash, wt%, ASTM D 874	0.9
Total Base Number, mg KOH/g, ASTM D 2896	9.8